NSN 5930-01-230-5342

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-230-5342

Body Style:
Hole mounted
Overall Length:
20.0 millimeters
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
24.0 millimeters
Overall Width:
7.0 millimeters
Body Length:
0.780 inches
Body Width:
0.250 inches
Body Height:
0.370 inches
Unthreaded Mounting Hole Diameter:
0.089 inches
Actuator Length:
0.092 inches
Actuator Style:
Rectangular
Actuator Height:
10.3 millimeters
Actuator Width:
0.122 inches
Actuator Free Position Height:
17.8 millimeters
Actuator Adapter Style:
Roller arm
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Actuating Force:
1.4 newtons

1.4 newtons

Actuator Movement:

0.1 differential millimeters and 9.4 pretravel millimeters

NSN 5930-01-230-5342

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive ac
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

No

Fiig:

A053a0

Demilitarization: