NSN 5930-01-230-5508

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-230-5508

| view Offinite at https://aerobasegroup.com/hist//3330-01-230-3300 |
|--|
| Body Style: |
| Panel mount |
| Overall Length: |
| 1.000 inches |
| Overall Height: |
| 3.050 inches |
| Overall Width: |
| 1.000 inches |
| Body Length: |
| 0.688 inches |
| Body Width: |
| 0.688 inches |
| Body Height: |
| 2.600 inches |
| Actuator Length: |
| 0.620 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.150 inches |
| Actuator Width: |
| 0.620 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| White single actuator |
| Actuator Inscription: |
| Start test single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| End Application: |
| Countermeasures set an/alq-141 |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Nonpile-up Contact Arrangement: |
| 3 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes |

Precious Material And Location:

inductive ac and 2.000 amperes lamp ac

Contacts silver

NSN 5930-01-230-5508

Push Switch - Page 2 of 2



| Terminal Type And Quantity | /: |
|----------------------------|----|
|----------------------------|----|

5 tab, solder lug and 9 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0