## NSN 5930-01-231-3376

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-231-3376

Body Style:
Bushing mounted
Overall Length:
0.510 inches
Overall Height:
1.610 inches
Bushing Length:
0.280 inches
Body Length:
0.510 inches
Body Width:
0.510 inches
Body Height:
0.690 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
End Application:
Satellite communications set an/wsc-6 v
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
40
Thread Size:
0.250 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
4.000 amperes resistive dc and 3.000 amperes resistive ac
Special Features:
Splashproof
Precious Material And Location:
Contacts silver and contacts and terminal surfaces gold
Unable To Decode:
Unable to decode and unable to decode
Thread Series Designator:
Uns
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a

## NSN 5930-01-231-3376

Push Switch - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A053a0