

View Online at <https://aerobasegroup.com/nsn/5930-01-231-4543>

**Body Style:**

Bushing mount

**Overall Length:**

2.150 inches

**Overall Height:**

2.375 inches

**Overall Width:**

0.750 inches

**Bushing Length:**

0.312 inches

**Body Length:**

1.336 inches

**Body Width:**

0.734 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.240 inches

**Actuator Height:**

0.563 inches

**Actuator Position-action Relationship:**

Center position maintained and left position momentary and right position momentary

**Maximum Voltage Rating In Volts:**

220.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

1.220 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Nonpile-up Contact Arrangement:**

1 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 8.000 amperes resistive ac and 5.000 amperes inductive ac and 2.500 amperes lamp ac

**Special Features:**

Mounting plate provided for panel mounting

**Terminal Type And Quantity:**

3 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0