

View Online at <https://aerobasegroup.com/nsn/5930-01-231-5287>

Thread Class:

2a single mounting facility

Thread Length:

0.640 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

2.050 inches

Overall Diameter:

1.370 inches

Individual Section Quantity:

1

Nonturn Device Type:

Key at 6: 00 o'clock

Operating Temperature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thready Qty Per Inch (tpi):

18 single mounting facility

Thread Size:

1.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at altitude

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at altitude and 2.5 amperes inductive load dc at altitude

Special Features:

O'ring shaft seal; fully enclosed

Style Designator:

Miniature, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0