## NSN 5930-01-232-0999

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-232-0999

| Body Style:                                                         |
|---------------------------------------------------------------------|
| Panel mount                                                         |
| Hazardous Locations/environmental Protection:                       |
| Moisture resistant                                                  |
| Body Length:                                                        |
| 0.740 inches                                                        |
| Body Width:                                                         |
| 0.740 inches                                                        |
| Body Height:                                                        |
| Between 1.380 inches and 1.450 inches                               |
| Case Material:                                                      |
| Plastic                                                             |
| Actuator Length:                                                    |
| 0.740 inches                                                        |
| Actuator Style:                                                     |
| Rectangular                                                         |
| Actuator Width:                                                     |
| 0.740 inches                                                        |
| Actuator Color:                                                     |
| White single actuator                                               |
| Maximum Voltage Rating In Volts:                                    |
| 250.0 ac and 30.0 dc                                                |
| Inclosure Type:                                                     |
| Fully enclosed                                                      |
| Mounting Method:                                                    |
| Panel                                                               |
| Features Provided:                                                  |
| Rfi shielding                                                       |
| Nonpile-up Contact Arrangement:                                     |
| 4 pole, double throw, both positions maintained single switch unit  |
| Contact Load Current Rating At Maximum Rated Voltage:               |
| 5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 |
| Precious Material And Location:                                     |
| Contact surfaces gold                                               |
| Terminal Type And Quantity:                                         |
| 17 pin                                                              |
| Shelf Life:                                                         |
| N/a                                                                 |
| Unit Of Measure:                                                    |
|                                                                     |
| Demilitarization:                                                   |
| No                                                                  |
|                                                                     |

amperes resistive ac

## NSN 5930-01-232-0999

Push Switch - Page 2 of 2

Fiig: A053a0

