NSN 5930-01-232-3621

Sensitive Switch - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5930-01-232-3621

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.690 inches
Body Length:
3.010 inches
Body Width:
1.020 inches
Body Height:
1.800 inches
Unthreaded Mounting Hole Diameter:
0.200 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.000 inches
Actuator Style:
Round
Actuator Diameter:
0.330 inches
Actuator Height:
1.560 inches
Maximum Voltage Rating In Volts:
125.0 ac
End Application:
2815-99-739-4949 engine, diesel paxman valenta model 16rp200m onboard 110 ft class coast guard vessels
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
6.0 ounces
Switch Actuating Force:
24.0 ounces
Actuator Movement:
0.040 pretravel inches and 0.180 overtravel inches and 0.003 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
15.000 amperes resistive ac and 15.000 amperes inductive ac
Terminal Type And Quantity:
3 screw
Shelf Life:

NSN 5930-01-232-3621

Sensitive Switch - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A053a0