NSN 5930-01-232-3621

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-232-3621

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.690 inches

Body Length:

3.010 inches

Body Width:

1.020 inches

Body Height:

1.800 inches

Unthreaded Mounting Hole Diameter:

0.200 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.000 inches

Actuator Style:

Round

Actuator Diameter:

0.330 inches

Actuator Height:

1.560 inches

Maximum Voltage Rating In Volts:

125.0 ac

End Application:

2815-99-739-4949 engine, diesel paxman valenta model 16rp200m onboard 110 ft class coast guard vessels

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

24.0 ounces

Actuator Movement:

0.040 pretravel inches and 0.180 overtravel inches and 0.003 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac and 15.000 amperes inductive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

NSN 5930-01-232-3621

Sensitive Switch - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0

