NSN 5930-01-232-4726

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-232-4726

| view offilite at https://aerobasegroup.com/histi/03300-01-232-4720 |
|---|
| Body Style: |
| Panel mount |
| Overall Length: |
| 1.210 inches |
| Overall Height: |
| 3.320 inches |
| Overall Width: |
| Between 0.950 inches and 0.970 inches |
| Body Length: |
| 1.200 inches |
| Body Width: |
| Between 0.950 inches and 0.970 inches |
| Body Height: |
| 3.110 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| Between 1.020 inches and 1.050 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| Between 0.164 inches and 0.210 inches |
| Actuator Width: |
| Between 0.720 inches and 0.750 inches |
| Actuator Color: |
| White single actuator and white single actuator |
| Illuminated Actuator Color: |
| White single actuator and white single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Rfi shielding |
| Nonpile-up Contact Arrangement: |
| 4 pole, double throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac |
| Special Features: |

Vertical split lens

NSN 5930-01-232-4726

Push Switch - Page 2 of 2



| Precious | Material | ∆nd ∣ | Location: |
|----------|----------|-------|-----------|
| | | | |

Rfi screen surfaces and contacts silver

Terminal Type And Quantity:

12 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0