## NSN 5930-01-232-8715

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-232-8715



## **Body Style:**

Panel mounted

## Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

## **Overall Length:**

3.266 inches

#### **Overall Height:**

0.812 inches

## **Overall Width:**

0.812 inches

#### **Body Width:**

0.750 inches

#### **Body Height:**

0.750 inches

#### Actuator Length:

## 0.812 inches

Actuator Style:

Rectangular

## Actuator Height:

0.270 inches

## Actuator Width:

0.812 inches

## Actuator Color:

White single actuator

## **Illuminated Actuator Color:**

White single actuator

#### **Actuator Inscription:**

C single actuator

#### Maximum Voltage Rating In Volts:

28.0 dc

## Mounting Surface To Terminal End Distance:

2.756 inches

Inclosure Type:

Fully enclosed

## **Mounting Method:**

Panel

## **Features Provided:**

Actuator seal and full display lens

## Nonpile-up Contact Arrangement:

2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

## Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

# NSN 5930-01-232-8715

Push Switch - Page 2 of 2

Special Features:

Emi shielded

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0

