# NSN 5930-01-232-9564

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-232-9564

# Thread Class:

2a single mounting facility

# Thread Length:

0.250 inches single mounting facility

# Hazardous Locations/environmental Protection:

Explosion proof

### **Overall Length:**

1.338 inches

#### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.093 inches single actuator

#### Shaft Diameter:

0.125 inches single actuator

#### Shaft Length:

## 0.375 inches single actuator

**Overall Diameter:** 

0.500 inches

## Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

# Operating Tempurature Range:

-65.0/+85.0 degrees celsius

#### **End Application:**

5841-01-054-8540 detecting set, radar signal an/apr-39 (v) 2

## Switch Contact Basic Design:

Nonpile-up symmetrical

## **Pole Quantity:**

1 single section rear

#### **Throw Quantity:**

6 single section rear

## **Mounting Method:**

Threaded bushing single mounting facility

## **Thread Size:**

0.250 inches single mounting facility

# Contact Voltage Rating In Volts:

28.0 dc at sea level

# Switch Actuator Indexing Position Quantity:

6 single actuator

## Shaft Type:

Round, flatted single actuator

# NSN 5930-01-232-9564

Rotary Switch - Page 2 of 2



# **Terminal Type:**

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

# **Contact Load Current Rating:**

200.0 milliamperes resistive load dc at sea level and 30.0 milliamperes inductive load dc at sea level and 100.0 milliamperes lamp load dc at sea level

Style Designator:

Snap or line

#### **Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Thread Series Designator:**

Unf single mounting facility

# **Specification Data:**

81349-mil-s-3786/20 government specification

Shelf Life:

N/a

Unit Of Measure:

# Demilitarization:

No

--

# Fiig:

A052b0