

View Online at <https://aerobasegroup.com/nsn/5930-01-232-9584>

**Body Style:**

Bushing mounted

**Body Diameter:**

0.640 inches

**Bushing Length:**

0.425 inches

**Body Length:**

1.040 inches

**Actuator Length:**

0.500 inches

**Actuator Style:**

Rectangular

**Actuator Width:**

0.500 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

White single actuator

**Actuator Inscription:**

4 single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

**Precious Material And Location:**

Contacts silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

2 tab, solder lug and 3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0