

View Online at <https://aerobasegroup.com/nsn/5930-01-233-2329>

Thread Class:

2a single mounting facility

Overall Length:

5.340 inches

Overall Height:

2.910 inches

Overall Width:

2.810 inches

Shaft Length:

2.440 inches single actuator

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.180 inches single mounting facility

End Application:

Used on switchboard ships service generator onboard 210 wmec a and b class c.G. Vessels

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

7 each section rear

Mounting Method:

Threaded hole single mounting facility

Cubic Measure:

0.014 cubic inches

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

600.0 ac at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

7 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.187 inches single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

30.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0