NSN 5930-01-233-4183



Rotary Switch - Page 1 of 2	G
View Online at https://aerobasegroup.com/nsn/5930-01-233-4183	
Thread Class:	
2b single mounting facility	
Hazardous Locations/environmental Protection:	
NV	

Waterproof

Overall Length:

5.090 inches

Overall Height:

2.810 inches

Overall Width:

2.810 inches

Individual Section Quantity:

4

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

1.625 inches single mounting facility

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Precious Material And Location:

Contact and rotor blade surfaces silver

NSN 5930-01-233-4183

Rotary Switch - Page 2 of 2



Precious Material:	
Silver	
Style Designator:	
Tap, circuit selector	
Thread Series Designator:	
Unc single mounting facility	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Fiig: A052b0