

View Online at <https://aerobasegroup.com/nsn/5930-01-233-4269>

**Body Style:**

Bushing mount

**Overall Length:**

1.686 inches

**Overall Height:**

2.718 inches

**Overall Width:**

1.336 inches

**Bushing Length:**

0.469 inches

**Body Length:**

1.686 inches

**Body Width:**

1.336 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.430 inches

**Actuator Height:**

0.921 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary

**Actuator Position-locking Relationship:**

Up position locked in and down position no locking action

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Mounting Surface To Terminal End Distance:**

1.328 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, single throw, normally closed, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

50.000 milliamperes resistive dc and 10.000 amperes resistive ac and 7.000 amperes inductive ac

**Test Data Document:**

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

8 tab w/screw

**Specification Data:**

96906-ms24614 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0