

View Online at <https://aerobasegroup.com/nsn/5930-01-233-9215>

Thread Class:

2b 1st mounting facility

Thread Length:

0.375 inches 2nd mounting facility

Overall Length:

9.000 inches

Overall Height:

3.250 inches

Overall Width:

3.250 inches

Individual Section Quantity:

7

Longest Horizontal Distance Between Mounting Centers:

2.000 inches 1st mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches 1st mounting facility

Longest Vertical Distance Between Mounting Centers:

2.180 inches 1st mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing 2nd mounting facility

Features Provided:

Actuator knob

Thread Size:

0.625 inches 2nd mounting facility

Contact Voltage Rating In Volts:

500.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Isosceles triangle 1st mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Screw

Contact Switching Action:

Makes before breaks 5th section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unf 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0