

View Online at <https://aerobasegroup.com/nsn/5930-01-233-9216>

**Thread Class:**

2b 1st mounting facility

**Thread Length:**

0.375 inches 2nd mounting facility

**Overall Length:**

12.190 inches

**Overall Height:**

3.250 inches

**Overall Width:**

3.250 inches

**Individual Section Quantity:**

12

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches 1st mounting facility

**Shortest Horizontal Distance Between Mounting Centers:**

1.000 inches 1st mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.180 inches 1st mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing 2nd mounting facility

**Features Provided:**

Actuator knob

**Thread Size:**

0.625 inches 2nd mounting facility

**Contact Voltage Rating In Volts:**

500.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Isosceles triangle 1st mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Terminal Type:**

Screw

**Contact Switching Action:**

Makes before breaks 2nd section periphery

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load highest ac voltage rating at sea level

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unf 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0