

View Online at <https://aerobasegroup.com/nsn/5930-01-233-9330>

Thread Class:

2b 2nd mounting facility

Thread Length:

0.375 inches 1st mounting facility

Overall Length:

8.563 inches

Overall Height:

3.500 inches

Overall Width:

4.375 inches

Unthreaded Mounting Hole Diameter:

0.312 inches 3rd mounting facility

Individual Section Quantity:

19

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

2 each section periphery

Mounting Facility Circle Radius:

1.610 inches 3rd mounting facility

Mounting Method:

Threaded bushing 1st mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

20 2nd mounting facility

Thread Size:

0.625 inches 1st mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position circular 3rd mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Special Features:

Item must comply with requirements of desc production standard no. L03500; for navy nuclear propulsion plant products only

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unef 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0