Pressure-thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-233-9505

Inside Diameter:

0.337 inches single connection

Overall Length:

7.913 inches

Overall Height:

3.110 inches

Overall Width:

2.047 inches

Body Height:

4.763 inches

Bulb Length:

1.968 inches

Bulb Diameter:

0.786 inches

End Application:

2815-99-739-4949 engine, diesel paxman model 16rp200m aboard 110 ft class coast guard vessels

Pressure Switch Type:

Gage

Tempurature Sensing Element Type:

Bulb

Mounting Method:

Immersion well

Features Provided:

Electrical access port

Contact Action Stimulus:

Decrease

Proof Pressure:

1500.00 pounds per square inch

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary

Terminal Type:

Screw

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+3.00/+54.00 actuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point shaft with scale

Contact Voltage Rating In Volts:

480.0 ac at sea level second voltage



Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A048b0