

View Online at <https://aerobasegroup.com/nsn/5930-01-233-9658>

Thread Class:

2a single mounting facility

Overall Length:

4.840 inches

Overall Height:

2.910 inches

Overall Width:

2.810 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.180 inches single mounting facility

End Application:

Used on s.S. Generator switchboard onboard 210 ft wmec "a" and "b" coast guard vessels

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

7 each section rear

Mounting Method:

Threaded hole single mounting facility

Cubic Measure:

39.577 cubic inches

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

600.0 ac at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

7 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

30.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0