## NSN 5930-01-233-9659

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-233-9659

**Thread Class:** 2a single mounting facility **Overall Length:** 6.040 inches **Overall Height:** 2.910 inches **Overall Width:** 2.810 inches **Shaft Length:** 3.600 inches single actuator **Individual Section Quantity:** 3 **Longest Horizontal Distance Between Mounting Centers:** 2.000 inches single mounting facility **Shortest Horizontal Distance Between Mounting Centers:** 1.000 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.180 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 each section rear **Throw Quantity:** 7 each section rear **Mounting Method:** Threaded hole single mounting facility **Cubic Measure:** 49.389 cubic inches Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 600.0 ac at sea level **Mounting Facility Pattern:** Isosceles triangle single mounting facility **Switch Actuator Indexing Position Quantity:** 7 single actuator **Shaft Type:** Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.188 inches single actuator

## **NSN 5930-01-233-9659**Rotary Switch - Page 2 of 2



Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
30.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unf single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0