

View Online at <https://aerobasegroup.com/nsn/5930-01-233-9822>

**Thread Class:**

2a single mounting facility

**Overall Length:**

3.740 inches

**Overall Height:**

2.910 inches

**Overall Width:**

2.810 inches

**Shaft Length:**

2.440 inches single actuator

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:**

1.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.180 inches single mounting facility

**End Application:**

Used on ships service generator switchboard onboard 210 ft wmec "a" and "b" class coast guard vessels

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Pole Quantity:**

2 single section rear

**Throw Quantity:**

7 single section rear

**Mounting Method:**

Threaded hole single mounting facility

**Cubic Measure:**

30.582 cubic inches

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

600.0 ac at sea level

**Mounting Facility Pattern:**

Isosceles triangle single mounting facility

**Switch Actuator Indexing Position Quantity:**

7 single actuator

**Shaft Type:**

Rectangular/square, threaded hole single actuator

**Square Shaft Size:**

0.188 inches single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

30.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0