NSN 5930-01-234-0564

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-234-0564

Thread Class:

2b single mounting facility

Overall Length:

4.313 inches

Overall Height:

4.125 inches

Overall Width:

3.812 inches

Individual Section Quantity:

4

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

1.610 inches single mounting facility

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

20 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

500.0 ac at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Criticality Code Justification:

Zzzy

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

30.0 amperes resistive load dc at sea level

Special Features:

Item must comply with requirements of defense supply center columbus production standard no. Lo3502

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

NSN 5930-01-234-0564

Rotary Switch - Page 2 of 2



Reference Number Differentiating Characteristics:

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing

and testing specifications available at the dla icp

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0