

View Online at <https://aerobasegroup.com/nsn/5930-01-234-6433>

Thread Class:

2b all threaded hole

Hazardous Locations/environmental Protection:

Weather resistant

Overall Length:

5.660 inches

Overall Height:

4.660 inches

Overall Width:

2.090 inches

Body Height:

3.250 inches

Distance Between Mounting Facility Centers:

1.000 inches

Pressure Switch Type:

Differential

Mounting Method:

Base and threaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Thread Size:

0.190 inches all threaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

2 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

0.5 amperes resistive load third voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+20.00/+100.00 actuation point pounds per square inch gage and +100.00/+425.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point knob with scale and external deactuation point knob with scale

Contact Voltage Rating In Volts:

240.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Thread Series Designator:

Unf all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0