

View Online at <https://aerobasegroup.com/nsn/5930-01-234-6436>

Thread Class:

2b 1st mounting facility

Thread Length:

0.440 inches 2nd mounting facility

Overall Length:

4.820 inches

Overall Diameter:

2.810 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.203 inches 1st mounting facility

Longest Vertical Distance Between Mounting Centers:

2.203 inches 1st mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

3 single section rear

Mounting Facility Circle Radius:

0.905 inches 2nd mounting facility

Mounting Method:

Threaded stud 2nd mounting facility

Features Provided:

Actuator knob and spring return

Thready Qty Per Inch (tpi):

24 1st mounting facility

Thread Size:

0.190 inches 2nd mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Mounting Facility Pattern:

Four position rectangular 1st mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

15.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unf 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0