

View Online at <https://aerobasegroup.com/nsn/5930-01-234-7215>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.938 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

2.344 inches

Overall Width:

0.688 inches

Bushing Length:

0.609 inches

Body Length:

1.938 inches

Body Width:

0.688 inches

Body Height:

1.032 inches

Unthreaded Mounting Hole Diameter:

1.141 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

2.000 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.188 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

3.0 ounces

Switch Actuating Force:

10.0 ounces

Actuator Movement:

Between 0.015 pretravel inches and 0.140 overtravel inches and 0.002 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes motor dc and 15.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0