NSN 5930-01-234-9642

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-234-9642

g	
Thread Class:	
2b single mounting facility	
Overall Length:	
5.840 inches	
Overall Height:	
2.810 inches	
Overall Width:	
2.810 inches	
Individual Section Quantity:	
5	
Switch Contact Basic Design:	
Nonpile-up symmetrical	
Pole Quantity:	
1 each section rear	
Throw Quantity:	
12 each section rear	
Mounting Facility Circle Radius:	
1.625 inches single mounting facility	
Mounting Method:	
Bracket single mounting facility and threaded hole single mounting facility	
Features Provided:	
Actuator knob	
Thready Qty Per Inch (tpi):	
24 single mounting facility	
Thread Size:	
0.190 inches single mounting facility	
Contact Voltage Rating In Volts:	
125.0 ac at sea level	
Mounting Facility Pattern:	
Four position circular single mounting facility	
Switch Actuator Indexing Position Quantity:	
12 single actuator	
Terminal Type:	
Screw	
Contact Switching Action:	
Breaks before makes each section rear	
Switch Actuator Positioning Increment:	
30.0 degrees single actuator	
Switch Actuator Stop Device Type:	
Fixed stop single actuator	
Contact Load Current Rating:	

7.5 amperes resistive load ac at sea level

NSN 5930-01-234-9642

Rotary Switch - Page 2 of 2



Style	Desig	nator:

Tap, circuit selector

Test Data Document:

81349-mil-s-21604 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single mounting facility

Specification Data:

81349-mil-s-21604/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0