NSN 5930-01-235-6677

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-235-6677

| view Online at https://aerobasegroup.com/nsn/0550-01-255-00// |
|---|
| Body Style: |
| Panel mount |
| Overall Length: |
| 1.210 inches |
| Overall Height: |
| 3.320 inches |
| Overall Width: |
| Between 0.950 inches and 0.970 inches |
| Body Length: |
| 0.660 inches |
| Body Width: |
| Between 0.950 inches and 0.970 inches |
| Body Height: |
| 3.110 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| Between 1.020 inches and 1.050 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| Between 0.164 inches and 0.210 inches |
| Actuator Width: |
| Between 0.720 inches and 0.750 inches |
| Actuator Color: |
| White single actuator |
| Actuator Inscription: |
| Left crank single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Rfi shielding |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac |

Special Features: Full display lens

NSN 5930-01-235-6677

Push Switch - Page 2 of 2



| recious | s iviateria | ı Ana | Location: |
|---------|-------------|-------|-----------|
| | | | |

Contacts silver

Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0