

View Online at <https://aerobasegroup.com/nsn/5930-01-235-8729>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Oiltight and watertight and dustproof and driptight

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.500 inches

**Actuator Free Position Height:**

0.500 inches

**Housing Height:**

2.438 inches

**Housing Length:**

4.500 inches

**Housing Width:**

2.312 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

4.219 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.812 inches

**Maximum Voltage Rating In Volts:**

575.0 ac and 600.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, both positions maintained single switch unit

**Switch Actuating Force:**

44.000 inch-ounces

**Actuator Movement:**

5.0 pretravel degrees and 25.0 overtravel degrees and 5.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0