

View Online at <https://aerobasegroup.com/nsn/5930-01-235-8729>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Oiltight and watertight and dustproof and driptight

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.500 inches

Actuator Free Position Height:

0.500 inches

Housing Height:

2.438 inches

Housing Length:

4.500 inches

Housing Width:

2.312 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

4.219 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.812 inches

Maximum Voltage Rating In Volts:

575.0 ac and 600.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, both positions maintained single switch unit

Switch Actuating Force:

44.000 inch-ounces

Actuator Movement:

5.0 pretravel degrees and 25.0 overtravel degrees and 5.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0