

View Online at <https://aerobasegroup.com/nsn/5930-01-235-8947>

Inside Diameter:

0.125 inches single connection

Overall Length:

3.188 inches

Overall Height:

5.250 inches

Overall Width:

2.500 inches

Body Height:

3.000 inches

Longest Horizontal Distance Between Mounting Centers:

2.625 inches

Longest Vertical Distance Between Mounting Centers:

2.438 inches

End Application:

Used on oil purifier model mapx-204-tgt-24-60 onboard 210 wmec a and b class coast guard vessels

Pressure Switch Type:

Gage

Mounting Method:

Threaded stud

Features Provided:

Electrical access port

Cubic Measure:

41.843 cubic inches

Thready Qty Per Inch (tpi):

27 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

1000.00 pounds per square inch gage

Thread Size:

0.125 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+0.60/+15.00 actuation point pounds per square inch gage and +0.50/+14.20 deactuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point hex nut and external deactuation point hex nut

Contact Voltage Rating In Volts:

125.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Special Features:

Pressure connector also external thread npt 0.500 inch 14 threads per inch

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0