

View Online at <https://aerobasegroup.com/nsn/5930-01-235-9745>

**Inside Diameter:**

0.250 inches single connection

**Overall Length:**

4.000 inches

**Overall Height:**

4.562 inches

**Overall Width:**

4.500 inches

**Body Length:**

3.500 inches

**Body Height:**

3.875 inches

**Pressure Switch Type:**

Absolute

**Operating Temperature Rating:**

Between 4.0 degrees fahrenheit and 140.0 degrees fahrenheit

**Mounting Method:**

Bracket

**Cubic Measure:**

64.000 cubic inches

**Contact Action Stimulus:**

Increase

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Quick disconnect, male

**Contact Load Current Rating:**

5.0 amperes resistive load first voltage

**Contact Adjustability:**

Actuation point adjustable or deactuation point adjustable

**Contact Adjustment Range:**

+6.00/+60.00 actuation point pounds per square inch and +6.00/+60.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

Internal actuation point hex nut or internal deactuation point hex nut

**Contact Voltage Rating In Volts:**

250.0 dc at sea level third voltage

**Pressure Connector Type:**

Inverted flare, threaded internal single connection

**Special Features:**

Item can accommodate interchangeable transducers? Also has a two-stage dual adjustment and it has a nema 3 and 4 watertight enclosure

**Media For Which Designed:**

Liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0