

View Online at <https://aerobasegroup.com/nsn/5930-01-236-0576>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.315 inches single mounting facility

**Overall Length:**

2.635 inches

**First Flat Length:**

1.500 inches single actuator

**Flat Height:**

0.217 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

1.500 inches single actuator

**Overall Diameter:**

1.031 inches

**Nonturn Device Radius:**

0.375 inches at 3:00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Pin at 3:00 o'clock

**Operating Temperature Range:**

-30.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

3 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

250.0 highest dc voltage rating at sea level

**Shaft Flat/slot Angular Location:**

0.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

350.0 milliamperes resistive load lowest dc voltage rating at sea level

**Precious Material And Location:**

Contact and terminal surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Snap or line

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0