

View Online at <https://aerobasegroup.com/nsn/5930-01-236-1488>

**Hazardous Locations/environmental Protection:**

Explosion proof and moisture resistant and salt spray resistant and sand proof and vibration proof

**Overall Length:**

0.842 inches

**Overall Height:**

1.770 inches

**Overall Width:**

1.150 inches

**Unthreaded Mounting Hole Diameter:**

0.080 inches single mounting facility

**Distance Between Mounting Facility Centers:**

0.905 inches single mounting facility

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Mounting Method:**

Base single mounting facility and unthreaded hole single mounting facility

**Actuator Type:**

Thumbwheel single actuator

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:**

16 single actuator

**Terminal Type:**

Printed circuit

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Readout Indicator Marking:**

Dud, a, ae, b, be, c, ce, d, de, sp1, sp2, sp3, sp4, sp5, sp6, mty single section

**Contact Arrangement Truth Table:**

Binary with common not-true bits, 2 pole - 16 positions single section

**Color:**

White single indicator marking

**Style Designator:**

Rectangular indicating

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0