## NSN 5930-01-236-6803

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-236-6803

#### **Thread Class:**

2b single mounting facility

#### Hazardous Locations/environmental Protection:

Waterproof

### **Overall Length:**

3.907 inches

#### **Overall Height:**

2.141 inches

#### **Overall Width:**

2.141 inches

#### Individual Section Quantity:

6

#### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

#### **Mounting Facility Circle Radius:**

#### 1.156 inches single mounting facility

#### **Mounting Method:**

Threaded hole single mounting facility and bracket single mounting facility

#### Features Provided:

Actuator knob

#### Thready Qty Per Inch (tpi):

28 single mounting facility

#### Thread Size:

0.190 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

120.0 dc at sea level

#### **Switch Actuator Momentary Position:**

Clockwise single actuator and counterclockwise single actuator

#### Mounting Facility Pattern:

Four position circular single mounting facility

#### Switch Actuator Indexing Position Quantity:

3 single actuator

#### **Terminal Type:**

Tab w/screw

#### **Switch Actuator Positioning Increment:**

90.0 degrees single actuator

#### **Contact Load Current Rating:**

10.0 amperes resistive load dc at sea level

#### **Special Features:**

Special mtg bracket

#### Style Designator:

Tap, circuit selector

# NSN 5930-01-236-6803

Rotary Switch - Page 2 of 2



Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

