

View Online at <https://aerobasegroup.com/nsn/5930-01-236-8141>

**Overall Length:**

7.000 inches

**Overall Width:**

3.250 inches

**Individual Section Quantity:**

3

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:**

1.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.187 inches single mounting facility

**Operating Temperature Range:**

-25.0/+125.0 degrees fahrenheit

**End Application:**

6115-01-143-3850 generator, alternating current

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob and legend plate and pull to turn and spring return

**Thready Qty Per Inch (tpi):**

24 single mounting facility

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

500.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Isosceles triangle single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Terminal Type:**

Screw

**Contact Switching Action:**

Makes before breaks 3rd section periphery

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load highest ac voltage rating at sea level

**Special Features:**

Red flag (close) and green flag (open) indicators

**Precious Material And Location:**

Contact and terminal surfaces silver

**Precious Material:**

Silver

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0