## NSN 5930-01-236-8142

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-236-8142

Overall Length:

6.000 inches

**Overall Width:** 

3.250 inches

**Individual Section Quantity:** 

3

**Longest Horizontal Distance Between Mounting Centers:** 

2.000 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:** 

1.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:** 

2.187 inches single mounting facility

**Operating Tempurature Range:** 

-25.0/+125.0 degrees fahrenheit

**End Application:** 

6115-01-143-3850 generator, alternating current

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Mounting Method:** 

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:** 

Actuator knob and legend plate

Thready Qty Per Inch (tpi):

24 single mounting facility

**Thread Size:** 

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:** 

500.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:** 

Isosceles triangle single mounting facility

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

**Terminal Type:** 

Screw

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Adjustable stop single actuator

**Contact Load Current Rating:** 

5.0 amperes resistive load highest ac voltage rating at sea level

**Special Features:** 

Legend plate marked synchroscope, off, on

## NSN 5930-01-236-8142

Rotary Switch - Page 2 of 2



<b>Precious Material And Location:</b>
Contact and rotor surfaces silver
Precious Material:
Silver
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0