NSN 5930-01-236-8142

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-236-8142

Overall Length:

6.000 inches

Overall Width:

3.250 inches

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.187 inches single mounting facility

Operating Tempurature Range:

-25.0/+125.0 degrees fahrenheit

End Application:

6115-01-143-3850 generator, alternating current

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob and legend plate

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

500.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Special Features:

Legend plate marked synchroscope, off, on

NSN 5930-01-236-8142

Rotary Switch - Page 2 of 2



Precious Material And Location:
Contact and rotor surfaces silver
Precious Material:
Silver
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0