

View Online at <https://aerobasegroup.com/nsn/5930-01-236-9011>

Hazardous Locations/environmental Protection:

Watertight and oiltight and dusttight

Overall Length:

4.000 inches

Overall Width:

2.312 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Longest Horizontal Distance Between Mounting Centers:

3.250 inches

Shortest Horizontal Distance Between Mounting Centers:

1.625 inches

Longest Vertical Distance Between Mounting Centers:

3.312 inches

Temperature Sensing Element Type:

Bulb

Operating Temperature Rating:

300.0 degrees fahrenheit

Mounting Method:

Threaded bushing and flange and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

14 single threaded bushing

Thread Size:

0.500 inches single threaded bushing

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

20.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+75.00/+205.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

250.0 ac at sea level second voltage

Thread Series Designator:

Npt single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0