## NSN 5930-01-236-9011

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-236-9011

## **Hazardous Locations/environmental Protection:**

Watertight and oiltight and dusttight

**Overall Length:** 

4.000 inches

Overall Width:

2.312 inches

**Unthreaded Mounting Hole Diameter:** 

0.203 inches

**Longest Horizontal Distance Between Mounting Centers:** 

3.250 inches

**Shortest Horizontal Distance Between Mounting Centers:** 

1.625 inches

**Longest Vertical Distance Between Mounting Centers:** 

3.312 inches

**Tempurature Sensing Element Type:** 

. .....

**Operating Tempurature Rating:** 

300.0 degrees fahrenheit

**Mounting Method:** 

Threaded bushing and flange and unthreaded hole

**Features Provided:** 

Electrical access port

Thready Qty Per Inch (tpi):

14 single threaded bushing

**Thread Size:** 

0.500 inches single threaded bushing

**Mounting Facility Pattern:** 

Isosceles triangle

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, one position momentary

**Terminal Type:** 

Tab w/screw

**Contact Load Current Rating:** 

20.0 amperes resistive load second voltage

**Contact Adjustability:** 

Actuation point adjustable

**Contact Adjustment Range:** 

+75.00/+205.00 actuation point degrees fahrenheit

**Contact Voltage Rating In Volts:** 

250.0 ac at sea level second voltage

**Thread Series Designator:** 

Npt single threaded bushing

## NSN 5930-01-236-9011

Thermostatic Switch - Page 2 of 2



	<b>L</b> -	16		ife	_
3	ne	п	_	пе	Ξ

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0