

View Online at <https://aerobasegroup.com/nsn/5930-01-237-2410>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

2.938 inches

Overall Height:

1.891 inches

Overall Width:

1.891 inches

Individual Section Quantity:

3

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

1.156 inches single mounting facility

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

480.0 highest ac voltage rating at sea level120.0 lowest ac voltage rating at sea level250.0 highest dc voltage rating at sea level125.0 lowest dc voltage rating at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level15.0 amperes resistive load lowest ac voltage rating at sea level5.0 amperes resistive load highest dc voltage rating at sea level10.0 amperes resistive load lowest dc voltage rating at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0