NSN 5930-01-237-2481

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-237-2481

Unthreaded Mounting Hole Diameter:
0.094 inches
Distance Between Mounting Facility Centers:
1.469 inches
End Application:
5895-01-183-9468 frame, front
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 450.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Automatic reset
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
6.0 amperes resistive load third voltage
Contact Adjustability:
Actuation point not adjustable
Contact Stimulus Rating:
175.00 actuation point degrees fahrenheit and 165.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
30.0 dc at sea level fourth voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Disc w/flange
Specification Data:
80063-a318560 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5930-01-237-2481

Thermostatic Switch - Page 2 of 2

Fiig: A048b0

