

View Online at <https://aerobasegroup.com/nsn/5930-01-237-3486>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Corrosion resistant and explosion proof

Overall Length:

0.750 inches

Overall Height:

2.320 inches

Overall Width:

0.750 inches

Body Length:

0.688 inches

Body Width:

0.750 inches

Body Height:

2.240 inches

Actuator Length:

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

0.150 inches

Actuator Width:

0.620 inches

Actuator Color:

Black single actuator and black single actuator

Illuminated Actuator Color:

Green single actuator and yellow single actuator

Actuator Inscription:

Valid inval single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc

Special Features:

Bulb size designator t-1, horizontal split lens

Precious Material And Location:

Contact and terminal surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0