

View Online at <https://aerobasegroup.com/nsn/5930-01-237-3486>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Corrosion resistant and explosion proof

**Overall Length:**

0.750 inches

**Overall Height:**

2.320 inches

**Overall Width:**

0.750 inches

**Body Length:**

0.688 inches

**Body Width:**

0.750 inches

**Body Height:**

2.240 inches

**Actuator Length:**

0.620 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.150 inches

**Actuator Width:**

0.620 inches

**Actuator Color:**

Black single actuator and black single actuator

**Illuminated Actuator Color:**

Green single actuator and yellow single actuator

**Actuator Inscription:**

Valid inval single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc

**Special Features:**

Bulb size designator t-1, horizontal split lens

**Precious Material And Location:**

Contact and terminal surfaces gold and contacts silver

**Unable To Decode:**

Unable to decode and unable to decode

**Terminal Type And Quantity:**

6 turret and 5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0