

View Online at <https://aerobasegroup.com/nsn/5930-01-237-3761>

Thread Class:

2b all threaded hole

Overall Width:

2.432 inches

Body Length:

1.830 inches

Body Height:

2.880 inches

Distance Between Mounting Facility Centers:

Between 1.209 inches and 1.229 inches

Capillary Tube Length:

72.0 inches

Bulb Length:

Between 10.000 inches and 12.000 inches

Bulb Diameter:

0.190 inches

End Application:

Kidd class ddg, tarawa class lha, forrestal class cv, ticonderoga class cg (47), wasp class lhd, spruance class dd (963), nimitz class cvn, oliver perry class ffg, los angeles class ssn (688).

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Bracket and threaded hole

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.164 inches all threaded hole

Mounting Facility Pattern:

Two position in-line

Criticality Code Justification:

Feat

Contact Load Current Rating:

25.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

159.00 actuation point degrees fahrenheit and 179.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Special Features:

Weapon system essential

Media For Which Designed:

Gas or liquid

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0