NSN 5930-01-237-7324

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-237-7324

Thread Class: 2b single mounting facility **Overall Length: 4.157 inches Overall Height:** 5.206 inches **Overall Width:** 2.812 inches **Individual Section Quantity:** 2 **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 each section periphery **Throw Quantity:** 8 each section periphery **Mounting Facility Circle Radius:** 1.625 inches single mounting facility **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 lowest dc voltage rating at sea level **Mounting Facility Pattern:** Four position circular single mounting facility **Switch Actuator Indexing Position Quantity:** 8 single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section periphery **Switch Actuator Positioning Increment:** 45.0 degrees single actuator **Switch Actuator Stop Device Type:**

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

NSN 5930-01-237-7324

Rotary Switch - Page 2 of 2



| Special | Features: |
|---------|-----------|
|---------|-----------|

Pistol-grip knob has built-in lock

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0