NSN 5930-01-237-7956

Push Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-01-237-7956

| Panel mount | | | | | |
|---|--|--|--|--|--|
| Overall Length: | | | | | |
| 1.200 inches | | | | | |
| Overall Height: | | | | | |
| 3.220 inches | | | | | |
| Overall Width: | | | | | |
| 0.960 inches | | | | | |
| Body Length: | | | | | |
| 1.090 inches | | | | | |
| Body Width: | | | | | |
| 0.850 inches | | | | | |
| Body Height: | | | | | |
| 3.080 inches | | | | | |
| Actuator Length: | | | | | |
| 1.040 inches | | | | | |
| Actuator Style: | | | | | |
| Rectangular | | | | | |
| Actuator Height: | | | | | |
| 0.140 inches | | | | | |
| Actuator Width: | | | | | |
| 0.800 inches | | | | | |
| Actuator Color: | | | | | |
| White single actuator | | | | | |
| Illuminated Actuator Color: | | | | | |
| White single actuator | | | | | |
| Actuator Inscription: | | | | | |
| On single actuator | | | | | |
| Maximum Voltage Rating In Volts: | | | | | |
| 250.0 ac and 30.0 dc | | | | | |
| Inclosure Type: | | | | | |
| Uninclosed | | | | | |
| Mounting Method: | | | | | |
| Panel | | | | | |
| Nonpile-up Contact Arrangement: | | | | | |
| 2 pole, double throw, both positions maintained single switch unit | | | | | |
| Contact Load Current Rating At Maximum Rated Voltage: | | | | | |
| 5.000 amperes resistive dc and 3.000 amperes inductive dc and 10.000 amperes resistive ac | | | | | |
| Precious Material And Location: | | | | | |
| Contacts silver | | | | | |
| Terminal Type And Quantity: | | | | | |
| 6 turret and 5 tab, solder lug | | | | | |

NSN 5930-01-237-7956

Push Switch - Page 2 of 2



| _ | | | | | |
|---|----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0