## NSN 5930-01-237-9966

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-237-9966

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.580 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.980 inches
Overall Height:
10.680 inches
Overall Width:
0.630 inches
Body Length:
1.580 inches
Body Width:
0.630 inches
Body Height:
1.740 inches
Unthreaded Mounting Hole Diameter:
0.200 inches
Actuator Style:
Flexible
Actuator Diameter:
0.070 inches
Actuator Height:
8.940 inches
Maximum Voltage Rating In Volts:
240.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Actuating Force:
2.0 ounces
Contact Load Current Rating At Maximum Rated Voltage:
3.000 amperes resistive dc and 5.000 amperes resistive ac and 1.200 amperes inductive ac
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5930-01-237-9966

Sensitive Switch - Page 2 of 2



em			

No

Fiig:

A053a0