## NSN 5930-01-237-9979

Push Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-01-237-9979   |
|---|
| Body Style:   |
| Panel mount   |
| Hazardous Locations/environmental Protection:   |
| Salt spray resistant and moisture resistant and explosion proof   |
| Overall Length:   |
| 0.750 inches  |
| Overall Height:   |
| 2.010 inches  |
| Overall Width:  |
| 0.750 inches  |
| Body Length:  |
| 0.688 inches  |
| Body Width:   |
| 0.688 inches  |
| Case Material:  |
| Metal   |
| Actuator Length:  |
| 0.620 inches  |
| Actuator Style:   |
| Rectangular   |
| Actuator Height:  |
| 0.125 inches  |
| Actuator Width:   |
| 0.620 inches  |
| Actuator Color:   |
| Black single actuator   |
| Illuminated Actuator Color:   |
| Amber single actuator   |
| Actuator Inscription:   |
| Aft temp single actuator  |
| Maximum Voltage Rating In Volts:  |
| 115.0 ac and 28.0 dc  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Panel   |
| Nonpile-up Contact Arrangement:   |
| 1 pole, double throw, one position momentary single switch unit   |
| Contact Load Current Rating At Maximum Rated Voltage:   |
| 7 500 amperes resistive do and 5 000 amperes inductive do and 1 000 amperes lamp do and 5 000 amperes resistive ac and 3 500 ampere |

**Special Features:** T-1 lamp bulb size

inductive ac and 1.000 amperes lamp ac

## NSN 5930-01-237-9979

Push Switch - Page 2 of 2



| <b>Precious Material And Location:</b> |
|--|
| Contacts silver                        |
| Terminal Type And Quantity:            |
| 3 turret and 6 tab, solder lug         |
| Shelf Life:                            |
| N/a                                    |
| Unit Of Measure:                       |
|  |
| Demilitarization:                      |
| No                                     |

**Fiig:** A053a0