## NSN 5930-01-237-9980

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-237-9980
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Salt spray resistant and moisture resistant and explosion proof
Overall Length:
0.750 inches
Overall Height:
2.010 inches
Overall Width:
0.750 inches
Body Length:
0.688 inches
Body Width:
0.688 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.125 inches
Actuator Width:
0.620 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Red single actuator
Actuator Inscription:
L engine fire single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes

**Special Features:** T-1 lamp bulb size

inductive ac and 1.000 amperes lamp ac

## NSN 5930-01-237-9980

Push Switch - Page 2 of 2



Precious Material And Location
--------------------------------

Contacts silver

**Terminal Type And Quantity:** 

3 turret and 6 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0